



Buzzsaw XL

Drilling Specifications

Pin Position

| | | | |
|---|---|---|-------------------------------|
| <p>The Buzzsaw's 12:00 pin, relative to the CG, makes this ball driller friendly for right & leftand bowlers.</p> | <p>Turning the pin towards 3 O'clock, relative to the CG, will increase length.</p> | <p>Turning the pin towards 9 O'clock, relative to the CG, will decrease length.</p> | <p>Pin distance from axis</p> |
|---|---|---|-------------------------------|

Drilling Recommendations

| | | | |
|--|---|---|--|
| <p>Label</p> <p>Length 7 Back-end 8</p> | <p>Label</p> <p>Length 2 Back-end 2</p> | <p>Max Leverage</p> <p>Length 5 Back-end 10</p> | <p>CG Out Leverage</p> <p>Length 3 Back-end 6</p> |
| <p>Thumb Leverage</p> <p>Length 4 Back-end 9</p> | <p>CG Axis</p> <p>Length 5 Back-end 7</p> | <p>Pin Axis</p> <p>Length 10 Back-end 4</p> | <p>Notes</p> <ol style="list-style-type: none"> 1. Pos. side, finger, & top wt., increase length and back-end. 2. Neg. side, thumb, & bottom, decrease length and back-end. 3. Axis holes decrease flare and back-end reaction. 4. Pin-in balls decrease length. 5. Pin-out balls increase length and flip. 6. If ending center of gravity is on your pin, CG or on the same rotational plane as those, reaction is enhanced. |